TYPE-C 6PIN-板上四脚插SMT无弹(独立中夹片2.0版本)

Kinghelm®





NOTE:
1.MATERIAL SPECIFICATION:
1-1.HOUSING:HIGH TEMPERATURE RESISTANT PLASTIC,UL94 V-0.
1-2.TERMINAL: COPPER ALLOY
1-3.FRONT SHELL: STAINLESS STEEL
1-4.MID PLATE: STAINLESS STEEL
2.PLATING SPECIFICATION:
2-1.TERMINAL:
Ni 50u" MIN. UNDER PLATED OVER ALL.
Au PLATED 0.5~1u" OVER Ni
2-2.FRONT SHELL:
NI 50u" MIN. PLATED OVER ALL.
3.MECHANICAL PERFORMANCE,
3-1.INSERTION FORCE: 0.5~2.0kgf.
3-2.REMOVAL FORCE: 0.6kgf~2.0kgf.
3-3.DURABILITY: 10000 CYCLES.
4.ELECTRICAL PERFORMANCE,
4-1. VOLTAGE RATING: 5.0V DC/AC
CURRENT RATING: 2.0A
4-2. LLCR: 50mΩ/PIN MAX.
4-3.INSULATION RESISTANCE: 100MΩ MIN
4-4.DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1 MINUTE.
5. ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -25°C~+85°C.

尺寸参数 / PRODUCT DIMENSION

Kinghelm®







PIN ASSIGNMENTS

A1	GND	B9	VBUS
A5	CC1	B5	CC2
A12	GND	B4	VBUS
PIN	SIGNAL NAME	PIN	SIGNAL NAME

L L =6.8
L L =6.5

TOLERANCE		NAME(INTENDED USE)	深圳市金航标电子有限公司	www.kinghelm.com.cn
		CUSTOMER DRAWING	KH-TYPE-C-6P	0755-28190160
X.X ±0.30	X.° ±10'	PART NO.	TITLE: TYPE-C 6PIN-板上四脚插SMT无弹(独立中夹片2.0版本)	
.XX ±0.20	.X' ± 6'	HYS		
.XXX ±0.10	.XX' ± 5'			
UNITS	mm	DESIGN: DRAW		
MATERILA		CHED: CHECK		
FINISH		APPD: APPROVED	SCALE 1:1	SHEET 1/2 REV. V0

包装规范 / PACKING SPECIFICATION







	REEL	CARTON
CONNECTOR (PCS)	1000	10000

TOLERANCE		NAME(INTENDED USE)	深圳市金航标电子有限公司	www.kinghelm.com.cn
		CUSTOMER DRAWING	KH-TYPE-C-6P	0755-28190160
X.X ±0.30	X.° ±10'	PART NO.	TITLE: TYPE-C 6PIN-板上四脚插SMT无弹(独立中夹片2.0版本)	
.XX ±0.20	.X' ± 6'	HYS		
.XXX ±0.10	.XX' ± 5'			
UNITS	mm	DESIGN: DRAW	DRAWG NO.	
MATERILA		CHED: CHECK		
FINISH		APPD: APPROVED	SCALE 1:1	SHEET 2/2 REV. V0