



规格说明:Specifications:

电气特性:Electrical:

1. 额定电流: Current Rating  
1.5A/contact terminal
2. 额定电压: Voltage Rating  
30V DC
3. 接触阻抗: Contact Resistance  
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voitage:  
500 V AC AT Sea Level
5. 绝缘阻抗: Lnsulation Resistance:  
1000MEGA ohms MIN

物理性能:Mechanical:

1. 插拔力: Cnncetor Mate and Unmate Force  
Mate force:3.57kgf(MAX)  
Unmate force:1.02kgf(MIN)
2. 端子保持力: Terminal Retenion

原材料:Material:

1. 塑胶:Housing:  
Hing Temperature Thermaplastics,  
PBT White/Black
2. 端子:Contact:Copper Alloy C2680
3. 外壳:Shell: Copper Alloy C2680/SPCC

电镀:Finish:

1. 端子:Contact: Plated Gold in Mating Area;  
Tin On Solder Talls
2. 外壳:Shell:  
Nickel Plating

RBCOMMENDBD P. C. B PATTBRN LA360 OUT

深圳市金航标电子有限公司	www.kinghelm.com.cn
KH-2AF1804ZJ-14.2JB	0755-83044319

UNLESS OTHERWISE SPECIFIED TOLERANCE .X ±0.20 .XX ±0.15 .XXX ±0.10 ANG. ±2°	DRAWN H.Q.huocv	UNIT MM	TITLE		
	APPROVED		SCALE 3/1	PART NO.	
	DATE 2011.03.18	SIZE A4	DOC. NO.		REV. A